



Applications

- Offices
- Hotels
- Industries
- Malls

Products Code	Watt rating	Lumens	l/m WATT	CRI	CCT	Pf	Beam Angle	SV in KV	THd	IP rating	Lifetime	Base	Body type	Size in mm	Packing
LUA6 10 AL-PC	10	1100	110	>80	6500	>0.9+	180	2.5	<15%	IP 20	35 K Hrs	RF/SM	AL/PC	600	12
LUA6 18 AL-PC	18	1980	110	>80	6500	>0.9+	180	2.5	<15%	IP 20	35 K Hrs	RF/SM	AL/PC	1200	12
LUA6 22 AL-PC	22	2420	110	>80	6500	>0.9+	180	2.5	<15%	IP 20	35 K Hrs	RF/SM	AL/PC	1200	12

Products Code	Watt rating	Lumens	l/m WATT	CRI	CCT	Pf	Beam Angle	SV in KV	THd	IP rating	Lifetime	Base	Body type	Size in mm	Packing
LUA7 24	24	2640	110	>80	6500	>0.9+	120	2.5	<15%	IP 20	35 K Hrs	CS/SM	MS/PC	600X600	10
LUA7 36	36	3960	110	>80	6500	>0.9+	120	2.5	<15%	IP 20	35 K Hrs	CS/SM	MS/PC	600X600	10
LUA7 45	45	4950	110	>80	6500	>0.9+	120	2.5	<15%	IP 20	35 K Hrs	CS/SM	MS/PC	600X600	10



Applications

- Offices
- Hotels
- Residential
- \* Commercial
- Malls

\*CCT available on demand (4500, 3000, 2700)

SVP: Surge Voltage Protection

Al : Aluminium

SM: Surface Mounting

CS: Ceiling Suspended

MS: Mild Steel with Powder coating