



Products Code	Watt rating	Lumens	l/m WATT	CRI	CCT	Pf	Beam Angle	SV in KV	THd	IP rating	Lifetime	Base	Body type	Size in mm	Packing
LUA1 06 R	6	600	100+	>80	6500	>0.9+	120	2.5	<15%	IP20	35 K Hrs	CS	ADC/PC	85	20
LUA1 06 S	6	600	100+	>80	6500	>0.9+	120	2.5	<15%	IP20	35 K Hrs	CS	ADC/PC	85	20
LUA1 09 R	9	900	100+	>80	6500	>0.9+	120	2.5	<15%	IP20	35 K Hrs	CS	ADC/PC	112	10
LUA1 09 S	9	900	100+	>80	6500	>0.9+	120	2.5	<15%	IP20	35 K Hrs	CS	ADC/PC	112	10
LUA1 12 R	12	1200	100+	>80	6500	>0.9+	120	2.5	<15%	IP20	35 K Hrs	CS	ADC/PC	112	10
LUA1 12 S	12	1200	100+	>80	6500	>0.9+	120	2.5	<15%	IP20	35 K Hrs	CS	ADC/PC	112	10



*CCT available on demand (4500, 3000, 2700)
SVP: Surge Voltage Protection
ADC: Aluminium Die Casting
CS: Ceiling Suspended
PC : Poly Carbonate



Applications

- Offices
- Showrooms
- Malls
- * Residence