



तमसो मा ज्योतिर्गमय
Leading from Darkness to Light

Flood Lights



Products Code	Watt rating	Lumens	l/m WATT	CRI	CCT	Pf	Beam Angle	SV in KV	THd	IP rating	Lifetime	Base	Body type	Size in mm	Packing
LUA3 10	10	1200	120	>70	6500	>0.9+	120	2.5-10	<15%	IP67	35 K Hrs	SM	ADC	170X110	12
LUA3 20	20	2400	120	>70	6500	>0.9+	120	2.5-10	<15%	IP67	35 K Hrs	SM	ADC	170X110	12
LUA3 30	30	3600	120	>70	6500	>0.9+	120	2.5-10	<15%	IP67	35 K Hrs	SM	ADC	170X110	12
LUA3 50	50	6000	120	>70	6500	>0.9+	120	2.5-10	<15%	IP67	35 K Hrs	SM	ADC	210X155	10
LUA3 70	70	8400	120	>70	6500	>0.9+	120	2.5-10	<15%	IP67	35 K Hrs	SM	ADC	210X155	10

*CCT available on demand (4500, 3000, 2700)

SVP: Surge Voltage Protection

ADC: Aluminium Die Casting

SM: Surface Mounting

Applications

- Industrial
- Construction
- Play grounds / Stadium
- Architechural Lighting
- Outdoor Events

