



तमसो मा ज्योतिर्गमय  
Leading from Darkness to Light

# Range of Products

Products	Down Light			Bulbs			Flood Light					Street Light						HIGH BAY & LOW BAY			Tube light			Panel		
Shape / type	Round/Square						Rectangular					Oval shape									2 & 4 Ft length			Square / Round		
Wattage	6	9	12	7	9	12	10	20	30	50	70	10	20	50	60	90	120	70	90	120	10	18	22	24	36	45
Product Code	LUA1 06	LUA1 09	LUA1 12	LUA2 07	LUA2 09	LUA2 12	LUA3 10	LUA3 20	LUA3 30	LUA3 50	LUA3 70	LUA4 10	LUA4 20	LUA4 50	LUA4 60	LUA4 90	LUA4 120	LUA5 70	LUA5 90	LUA5 120	LUA6 10	LUA6 18	LUA6 22	LUA7 24	LUA7 36	LUA7 45
CCT	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500
Lumens	600	900	1200	700	900	1200	1200	2400	3600	6000	8400	1200	2400	6000	7200	10800	14400	8400	10800	14400	1100	1980	2420	2640	3960	4950
Lumens/Watt	100	100	100	100	100	100	120	120	120	120	120	120	120	120	120	120	120	120	120	120	110	110	110	110	110	110
CRI	>80	>80	>80	>80	>80	>80	>70	>70	>70	>70	>70	>70	>70	>70	>70	>70	>70	>70	>70	>70	>80	>80	>80	>80	>80	>80
Power Factor	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+	>0.9+
Beam Angle	120	120	120	220	220	220	120	120	120	120	120	120	120	120	120	120	120	90/120	90/120	90/120	180	180	180	120	120	120
Base	CS	CS	CS	E27/B22	E27/B22	E27/B22	S M	S M	S M	S M	S M	PM	PM	PM	PM	PM	PM	CS	CS	CS	RF/SM	RF/SM	RF/SM	CS/SM	CS/SM	CS/SM
Body Type	ADC/PC	ADC/PC	ADC/PC	AL	AL	AL	ADC	ADC	ADC	ADC	ADC	ADC	ADC	ADC	ADC	ADC	ADC	AL	AL	AL	AL/PC	AL/PC	AL/PC	MS/PC	MS/PC	MS/PC
Size in mm	85	112	112	60x108	60x108	60x108	170x110	170x110	170x110	210x155	210x155	310x180	310x180	420x270	420x270	420x270	420x270	520x670	520x670	520x670	600	1200	1200	600x600	600x600	600x600
Thd	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%	<15%
I P	IP20	IP20	IP20	IP20	IP20	IP20	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Lifetime	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs	35 K Hrs
Packing	20	10	10	30	30	30	12	12	12	10	10	2	2	2	2	2	2	1	1	1	12	12	12	10	10	10
SVP in KV	2.5	2.5	2.5	2.5	2.5	2.5	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5-10	2.5	2.5	2.5	2.5	2.5	2.5
Thermal Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

\*CCT available on demand (4500, 3000, 2700)

SVP: Surge Voltage Protection

ADC: Aluminium Die Casting

Al : Aluminium

PC : Poly Carbonate

SM: Surface Mounting

PM: Pole Mounted

CS: Ceiling Suspended

RF: Retro Fit

MS: Mild Steel with Powder coating

Panel lights also available in 1200 mm length,

Color Option Available for all housing

All Light Fittings are With driver on board with